

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES


Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- BLURRY OR ILLEGIBLE TEXT
- SKEWED/SLATED IMAGES
- COLORED PHOTOS
- BLACK OR VERY DARK BLACK AND WHITE PHOTOS
- UNDECIPHERABLE GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

**As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.**



F.G. 1




FIG. 2

SERVER 150

APPLICATION LAYER	152
PRESENTATION LAYER	154
SESSION LAYER	156
TRANSPORT LAYER	158
NETWORK LAYER	160
DATA LINK LAYER	162
PHYSICAL LAYER	164

CLIENT 166

APPLICATION LAYER	152
PRESENTATION LAYER	154
SESSION LAYER	156
TRANSPORT LAYER	158
NETWORK LAYER	160
DATA LINK LAYER	162
PHYSICAL LAYER	164

FIG. 3




FIG. 4a






Fig. 4b



Example Network Top-level Devices GUI

↑
22°

Fig. 5



Alternative example of network top-level devices
GUI

↑
220

FIG. 6





Fig. 7



1394 and Non-1394 Network Scenario for address management

Fig. 8

Fig. 9a






Fig. 9b



DEVICES WITH USER INTERFACE






FIG. 10






Fig. 11



Example pictorial view of Network Top-level Devices UI Description

↑
250

FIG. 12



Example of network top-level devices GUI

↑
22°

FIG. 13